



**Customised Labelling Solutions** 

To Meet Your Needs

# Engineering Reliability & Performance

Made for high availability, repeatability, speed, volume, format flexibility, quick changeovers and robust longevity.

Production teams will achieve accuracy, consistency and minimal downtime or zero downtime (optional extra).

#### Servicing Australia

Have confidence in your machines & receive timely service. Local support teams are available in:

- O Sydney, NSW
- O Melbourne, VIC
- O Adelaide, SA
- O Brisbane, QLD
- O Perth, WA


# Friendly Customer Service

Understanding and support of the requirements to achieve production goals & improvements.

- Project Consultants
- Comprehensive Service Agreements
- Complete Training Programs
- Online Ordering System



# **Tronics S4**



#### **Touch Panel**

On the fly adjustments are simple and instantaneous. Store up to 50 jobs.
Operate up to 4 label heads.

#### **Individual Motors**

Consistent, accurate label placement. All modules contain individual motors that are fully synchronised with the main product conveyor.

#### **Zero Down Time Production**

# Add or Remove Modules

- O Bottle Separator
- Single Scroll (round bottles)
- Dual Scroll (oval bottle)
- Squaring Wheels

#### **Labelling Head**

- Adjustable brush assembly
- Adjustable web guides
- O Delrin/stainless peel plate
- Clear label gap detection

# **Customised Labelling Solutions**



#### **Quick Precise Changeovers**


All components can be adjusted with ease and precision using dial gauges. Quick job changeovers and minimal down time.

Select components feature quick-release adjustments. No tools required.

### **Flexibility & Custom Solutions**

Produce a final product that shines, Tronics machines are made for your needs.

Applications for round, oval, flat sided, tapered and more.



## **Label Specifications**

Label Min Thickness: 80micron

Label Reel Core Size: 76mm Inside Diameter

Label Reel Outside Diameter: 330mm

Label Reel Outside Diameter Max:

500mm (opt)

Label Min Size:

Vertical 15mm/Horizontal 20mm

Label Max Height: 110/210/260mm

Label Gap Min Size: 2.5mm

## **Labelling Head Specifications**

Dispensing Speed Min: 5m/min

Dispensing Speed Min: 30m/min (std)

Dispensing Speed Max: 60m/min (opt)

Missing Label Detection (opt)

Low-Level Roll Detection (opt)

Clear Label Gap Sensor (opt)

Label Verification (opt)

# **Conveyor System**

Speed: 6-30m/min

Conveyor Material:

Plastic/Stainless/Belt/Roller

Widths: 114/190/254mm

Conveyor with Pucks (non-std)

Servo Drive (std)

#### **Modules**

Wrap Module

Wrap Vacuum Module

Orientation System

Overhead Stabilising Conveyor

Single & Dual Scroll (High Speed Product Spacing) - Round and Oval Bottles

Aligner Chains

**Squaring Wheels** 

**Bottle Separator** 


Crash Gate System


Felt Wipes


Secondary Impression Rollers

Top and Bottom Label Placements

Side Grip Transfer System









aldus.com.au

Ph: 1300 018 330

Tronics
sales@tronics.com.au
Sydney NSW
Melbourne VIC
Brisbane QLD
Adelaide SA
Perth WA

Aldus-Graphics sales@aldusgraphics.com.au Sydney NSW Melbourne VIC Paragon Inks
info@paragoninks.com.au
Sydney NSW
Milford Astor

Milford Astor sales@astor.com.au Melbourne VIC Foilmakers sales@astor.com.au Melbourne VIC Adelaide SA