



CDIX
川达机械



河北川达机械制造有限公司
Hebei Chuanda Machinery Manufacturing Co., Ltd



CDJX CDJX
川达机械制造

DIRECTORY

目录

● 冻肉切丁机 CD300	2
● 冻肉切丁机CD440	3
● 冻肉切丁机 CD500	4
● 冻肉切片机 CD455	5
● 连续式切片机 CD430	6
● 二维切丁机 CDEW	7
● 小型冻肉切片机 CD280	8
● 连续砍排机 CDV280/CDV360	9
● 蔬菜切丁机 CD330	10
● 蔬菜切丁机 CD400	11
● 切菜机 CD190	12
● 多功能切菜机 CD500-I	13
● 切片切丝机 CDS	14
● 冻肉分块机 CDK455	15
● 冻肉分块机 CDL455	16
● 冻肉切块机 CDQ200	17
● 鲜肉切片机 CD600	18
● 拌馅机 CDF100/CDF250/CDF350/CDF650/CDF1200	19
● 全自动洗菜机 CD750	20
● 万能洗菜机 CD1000	22
● 去根机 CDG	23
● 土豆去皮机 CD50/CD100	24
● 输送机 CDZ-44	25

冻肉切丁机 CD300



技术参数

- 电压：三相380v 频率50Hz
- 内筒直径：300mm
- 最大物料尺寸：直径小于100mm
- 外形尺寸：1410x760x1208mm
- 整机材料：SUS304不锈钢
- 切割范围：5~12mm冻肉丁、丝、片
- 投料方式：连续
- 润滑方式：机体外油嘴
- 控制系统：PLC 触摸屏 变频器
- 总功率：7kW
- 产量：500~1000kg/h
- 重量：464kg
- 切割温度范围：-10℃~0℃
- 最佳切割温度：-6℃~-5℃
- 生产解冻环境温度：-8℃~-4℃
- 厚度调节：人工手动

性能介绍

- 先进的刀具拆卸方式
徒手拆卸刀组，不用任何工具
- 清洗方式
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
冻肉切丁、丝、片

Frozen Meat Dicer CD300

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customer's demands
- Power: 7kW
- Inner Drum Diameter: 300mm
- Capacity: 500~1000kg/h
- Max Input Material Size: Diameter less than 100mm
- Cutting Size Range: 5~12mm Frozen Meat Slices, Strips and Cubes
- External Dimension: 1410*760*1208mm
- Weight: 464kg
- Material of the Machine: SUS304 Stainless steel
- Cutting temperature for the frozen meat: -10℃~0℃
- Best Cutting Temperature for the frozen meat: -6℃~-5℃
- Meat Thaw Environment Temperature: -8℃~-4℃
- Material Input Way: Continuously
- Lubricating Way: Oil nozzle
- Thickness control: Manual Adjustment
- Control system: PLC, Touch screen, Frequency transformer

II Introduction:

- Advanced knife rollers disassembly way:
Workers could disassemble the knife rollers by hands, no need any tools
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Frozen Meat Slice, strips and Cubes

冻肉切丁机 CD440



技术参数

- 电压：三相380V 频率50Hz
- 内筒直径：440mm
- 最大物料尺寸：直径小于200mm
- 外形尺寸：2100x1300x2100mm
- 整机材料：SUS304不锈钢
- 重量：1500kg
- 投料方式：连续
- 润滑方式：机体外油嘴
- 控制系统：PLC 触摸屏 变频器
- 总功率：14.5kW
- 产量：1000~2000kg/h
- 切割范围：5~20mm冻肉丁、丝、片
- 切割温度范围：-10℃~0℃
- 最佳切割温度：-6℃~-5℃
- 生产解冻环境温度：-8℃~-4℃
- 厚度调节：触摸屏自动

性能介绍

- 先进的刀具拆卸方式
徒手拆卸刀组，不用任何工具
- 清洗方式
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
冻肉切丁、丝、片

Frozen Meat Dicer CD440

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customer's demands
- Power: 14.5kW
- Inner Drum Diameter: 440mm
- Capacity: 1000~2000kg/h
- Max Input Material Size: Diameter less than 200mm
- Cutting Size Range: 5~20mm Frozen Meat Slices, Strips and Cubes
- External Dimension: 2100*1300*2100mm
- Weight: 1500kg
- Material of the Machine: SUS304 Stainless steel
- Cutting temperature for the frozen meat: -10℃~0℃
- Best Cutting Temperature for the frozen meat: -6℃~-5℃
- Meat Thaw Environment Temperature: -8℃~-4℃
- Material Input Way: Continuously
- Lubricating Way: Oil nozzle
- Thickness control: Touch screen automatic
- Control system: PLC, Touch screen, Frequency transformer

II Introduction:

- Advanced knife rollers disassembly way:
Workers could disassemble the knife rollers by hands, no need any tools
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Frozen Meat Slice, strips and Cubes

冻肉切丁机 CD500



技术参数

- 电压：三相380v 频率50Hz
- 内筒直径：500mm
- 最大物料尺寸：直径小于130mm
- 外形尺寸：1630x1260x1840mm
- 整机材料：SUS304不锈钢
- 重量：1500kg
- 投料方式：连续
- 润滑方式：机体外油嘴
- 控制系统：PLC 触摸屏 变频器
- 总功率：14.5kW
- 产量：900~1500kg/h
- 切割范围：5~20mm冻肉丁、丝、片
- 切割温度范围：-10℃~0℃
- 最佳切割温度：-6℃~-5℃
- 生产解冻环境温度：-8℃~-4℃
- 厚度调节：触摸屏自动

性能介绍

- 先进的刀具拆卸方式
徒手拆卸刀组，不用任何工具
- 清洗方式
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
冻肉切丁、丝、片

Frozen Meat Dicer CD500

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customer's demands
- Power: 14.5kW
- Inner Drum Diameter: 500mm
- Capacity: 900~1500kg/h
- Max Input Material Size: Diameter less than 130mm
- Cutting Size Range: 5~20mm Frozen Meat Slices, Strips and Cubes
- External Dimension: 1630*1260*1840mm
- Weight: 1500kg
- Material of the Machine: SUS304 Stainless steel
- Cutting temperature for the frozen meat: -10℃~0℃
- Best Cutting Temperature for the frozen meat: -6℃~-5℃
- Meat Thaw Environment Temperature: -8℃~-4℃
- Material Input Way: Continuously
- Lubricating Way: Oil nozzle
- Thickness control: Touch screen automatic
- Control system: PLC, Touch screen, Frequency transformer

II Introduction:

- Advanced knife rollers disassembly way:
Workers could disassemble the knife rollers by hands, no need any tools
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Frozen Meat Slice, strips and Cubes

冻肉切片机 CD455



技术参数

- 电压：三相380V 频率50Hz
- 总功率：9.12kW
- 切刀速度：27~90次/分钟
- 切片厚度：0.3~700mm
- 最大物料尺寸：430×700mm
- 最大切割高度：185mm
- 外形尺寸：2100×1100×1800mm
- 切割温度范围：-10℃~0℃
- 整机材料：SUS304不锈钢
- 最佳切割温度：-6℃~-5℃
- 重量：988kg
- 生产解冻环境温度：-8℃~-4℃
- 放料方式：往复间断
- 润滑方式：机体油嘴
- 控制系统：PLC 触摸屏 变频器

性能介绍

- 先进的结构设计
六导柱直线定位运动切割结构
- 推料板可徒手拆卸清洗
- 下刃口磨损可更换
- 清洗方式
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
冻肉切片、条、块、卷

Frozen Meat Slicer CD455

I Technical Data:

- Voltage: 380V/50Hz/3phase or according to customer's demands
- Power: 9.12kW
- Knife Cutting Speed: 27~90times/minute
- Knife Cutting Thickness: 0.3~700mm
- Max Input Material Size: 430*700mm
- Max Cutting Height: 185mm
- External Dimension: 2100x1100x1800mm
- Weight: 988kg
- Machine Material: SUS304 Stainless steel
- Cutting temperature for the frozen meat: -10℃~0℃
- Best Cutting Temperature for the Frozen Meat: -6℃~-5℃
- Meat Thaw Environment Temperature: -8℃~-4℃
- Material Input Way: Put the material continuously
- Lubricating Way: Oil nozzle
- Control system: PLC, Touch screen, Frequency transformer

II Introduction:

- Advanced structure design:
Six Guide Pillar Straight-line Positioning Cutting Structure
- Pushing plate could be disassembled and cleaned by hands
- The lower edge is worn and replaceable
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Frozen Meat Slice, strips, blocks and rolls.

连续式切片机 CD430



技术参数

- 电压：三相380V 频率50Hz
- 切刀速度：27~90次/分钟
- 最宽物料尺寸：430mm
- 外形尺寸：2510x1060x1555 mm
- 整机材料：SUS304拉丝不锈钢
- 重量：1500kg
- 放料方式：连续
- 润滑方式：机体油嘴
- 控制系统：PLC 触摸屏 变频器
- 总功率：9.12kW
- 切割范围：3~1000mm 可调
- 最大切割高度：100mm
- 气源：0.2MPa
- 切割温度范围：-10℃~0℃
- 最佳切割温度：-6℃~-5℃
- 生产解冻环境温度：-8℃~-4℃

性能介绍

- 先进的切割方式
六导柱直线运动切割结构
- 先进的送料结构
上下传送带夹料输送，上压料带与物料接触面始终保持平面状态
- 下刃口磨损可更换
- 清洗方式：
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
冻肉切片、条、块

Continuous Frozen Meat Slicer CD430

I Technical Data:

- Voltage: 380V/50Hz/3phase or according to customer's demands
- Power: 9.12kW
- Air Source: 0.2MPa
- Knife Cutting Speed: 27~90times/minute
- Cutting Size: 3~1000mm Cubes, strips and slice
- Max Input Material Width: 430mm
- Max Cutting Height: 100mm
- External Dimension: 2510*1060*1555mm
- Weight: 1500kg
- Machine Material: SUS304 Wire drawing Stainless steel
- Cutting temperature for the frozen meat: -10℃~0℃
- Best Cutting Temperature for the Frozen Meat: -6℃~-5℃
- Meat Thaw Environment Temperature: -8℃~-4℃
- Material Input Way: Put the material continuously
- Lubricating Way: Oil nozzle
- Control system: PLC, Touch screen, Frequency transformer

II Introduction:

- Advanced cutting way:
Six Guide Pillar Straight-line Cutting Structure
- Advanced feeding-in structure:
Up and down conveyor belt press the meat and feeding-in, the up belt part connecting with the meat is always flat
- The lower edge is worn and replaceable
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Frozen Meat Slice, strips and big cubes.

二维切丁机 CDEW



技术参数

- 电压: 380V 频率50Hz
- 圆刀直径: 200mm
- 最宽物料尺寸: 430mm
- 外形尺寸: 2580x1130x1740mm
- 整机材料: SUS304拉丝不锈钢
- 重量: 1700kg
- 放料方式: 连续
- 润滑方式: 机体油嘴
- 控制系统: PLC 触摸屏 变频器
- 总功率: 12kW
- 切刀速度: 27~90次/min
- 最大切割高度: 50mm
- 切割温度范围: $-10^{\circ}\text{C} \sim 0^{\circ}\text{C}$
- 最佳切割温度: $-6^{\circ}\text{C} \sim -5^{\circ}\text{C}$
- 生产解冻环境温度: $-8^{\circ}\text{C} \sim -4^{\circ}\text{C}$

性能介绍

- 先进的切割结构设计
四导柱上下贯穿运动切割结构, 切条完成后刀架将条压入圆刀组成丁
- 先进的送料结构
上下传送带夹料输送, 上压料带与物料接触面始终保持平面状态
- 清洗方式
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
冻肉和麻冻肉的切片、条、块

Two-dimensional Frozen Meat Dicer CDEW

Technical Data:

- Voltage: 380V/50Hz/3phase or according to customer's demands
- Power: 12kW
- Circular knife diameter: 200mm
- Knife Cutting Speed: 27~90times/minute
- Max Input Material Width: 430mm
- Max Cutting Height: 50mm
- External Dimension: 2580*1130*1740mm
- Weight: 1700kg
- Machine Material: SUS304 Wire drawing Stainless steel
- Cutting temperature for the frozen meat: $-10^{\circ}\text{C} \sim 0^{\circ}\text{C}$
- Best Cutting Temperature for the Frozen Meat: $-6^{\circ}\text{C} \sim -5^{\circ}\text{C}$
- Meat Thaw Environment Temperature: $-8^{\circ}\text{C} \sim -4^{\circ}\text{C}$
- Material Input Way: Put the material continuously
- Lubricating Way: Oil nozzle
- Control system: PLC, Touch screen, Frequency transformer

II Introduction:

- Advanced cutting structure design:
Four Guide Pillar Up-and-down Cutting Structure, after cutting to strips, the blade carrier will press the strips into circular knife and cut into cubes.
- Advanced feeding-in structure:
Up and down conveyor belt press the meat and feeding-in, the up belt part connecting with the meat is always flat.
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Frozen Meat and Hemp Frozen Meat Slice, strips, cubes.

小型冻肉切片机 CD280



技术参数

- 电压：三相380V 频率50Hz
- 总功率：4.5kW
- 切刀速度：35~85次/分钟
- 切片厚度：0.5~100mm
- 最大物料尺寸：400x280mm
- 最大切割高度：180mm
- 外形尺寸：1050x745x1715mm
- 整机材料：SUS304不锈钢
- 切割温度范围：-10℃~0℃
- 重量：560kg
- 最佳切割温度：-6℃~-5℃
- 放料方式：往复间断
- 生产解冻环境温度：-8℃~-4℃
- 润滑方式：机体油嘴
- 控制系统：PLC 触摸屏 变频器

性能介绍

- 先进的结构设计
六导柱直线定位运动切割结构
- 推料板可徒手拆卸清洗
- 清洗方式
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
冻肉切片、条、块、卷

Frozen Meat Slicer CD280


I Technical Data:

- Voltage: 380V/50Hz/3phase or according to customer's demands
- Power: 4.5kW
- Knife Cutting Speed: 35~85times/minute
- Knife Cutting Thickness: 0.5~100mm
- Max Input Material Size: 400*280mm
- Max Cutting Height: 180mm
- External Dimension: 1050*745*1715mm
- Weight: 560kg
- Machine Material: SUS304 Stainless steel
- Cutting temperature for the frozen meat: -10℃~0℃
- Best Cutting Temperature for the Frozen Meat: -6℃~-5℃
- Meat Thaw Environment Temperature: -8℃~-4℃
- Material Input Way: Put the material continuously
- Lubricating Way: Oil nozzle
- Control system: PLC, Touch screen, Frequency transformer

II Introduction:

- Advanced structure design:
Six Guide Pillar Straight-line Positioning Cutting Structure
- Pushing plate could be disassembled and cleaned by hands
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Frozen Meat Slice, strips, blocks and rolls.

连续砍排机 CDV280/CDV360



技术参数

- 外形尺寸: 2490x1090x1440 mm/2600x1300x1700 mm
- 最大进料尺寸: 宽260mm, 高100mm / 宽360mm, 高140mm
- 重量: 1200公斤/1600公斤
- 功率: 5.5kW/7kW
- 切割尺寸: 1~50mm范围任意调整
- 生产量: 120~290刀/min / 160~320刀/min
- 放料方式: 连续
- 控制系统: PLC触摸屏 变频器 霍尔开关式
- 切割温度范围: $-6^{\circ}\text{C} \sim 0^{\circ}\text{C}$
- 生产解冻环境温度: $-6^{\circ}\text{C} \sim -3^{\circ}\text{C}$
- 最佳切割温度: $-4^{\circ}\text{C} \sim -3^{\circ}\text{C}$

性能介绍

- 切刀驱动:
由单独一台电机驱动, 用变频器控制, 根据物料调节切割刀速。
- 物料输送部分:
由一台伺服电机驱动, 根据需求, 在一定范围内随意调整输送速度。
- 用途:
肉类、骨类切片、切丝、切段, 切割范围1~50mm。

Continuous Cutting Machine CDV280/CDV360

I Technical Data:

- External dimension: 2490x1090x1440 mm/2600x1300x1700
- Power: 5.5kW/7kW
- Maximum feed size: W260mm, H100 / W360mm, H140
- Weight: 1200kg/1600kg
- Cutting temperature for the frozen meat: $-6^{\circ}\text{C} \sim 0^{\circ}\text{C}$
- Best Cutting Temperature for the Frozen Meat: $-4^{\circ}\text{C} \sim -3^{\circ}\text{C}$
- Meat Thaw Environment Temperature: $-6^{\circ}\text{C} \sim -3^{\circ}\text{C}$
- Knife cutting speed: 120~290 times/minute / 160~320times/minute
- Cutting size: 1~50mm
- Material Input Way: Put the material continuously
- Control system: PLCTouch screen, Frequency transformer, Hall switch

II Introduction:

- Cutting knife-driven:
driven by one single motor, controlled by frequency transformer, cutting speed is based on the material.
- Material transportation:
driven by one single servo motor, able to customize transportation speed base on demands
- Application:
meat, bones slicing, dicing, cutting range 1~50mm

蔬菜切丁机 CD330



技术参数

- 电压：三相380v 频率50Hz
- 内筒直径：330 mm
- 最大物料尺寸：直径小于120 mm
- 外形尺寸：1260x900x1700mm
- 整机材料：SUS304不锈钢
- 投料方式：连续
- 润滑方式：机体外油嘴
- 控制系统：防水按钮 PLC 变频器
- 总功率：4kW
- 产量：1000~3000kg/h
- 切割范围：3~20mm丁、丝、片
- 重量：500 kg
- 冻肉切割温度范围：-5℃~0℃
- 生产解冻环境温度：-6℃~-3℃
- 厚度调节：人工手动

性能介绍

- 采用变频器控制驱动电机
- 操作为按钮式操作
分为低速、中速、高速，可根据物料选择不同的切割速度

Vegetable Dicer CD330

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customer's demands
- Power: 4kW
- Inner Drum Diameter: 330mm
- Capacity: 1000~3000kg/h
- Max Input Material Size: Diameter less than 120mm
- Cutting Size Range: 3~12mm Vegetables Slices, Strips and Cubes
- External Dimension: 1260*900*1700mm
- Weight: 500kg
- Material of the Machine: SUS304 Stainless steel
- Cutting Temperature for the frozen meat: -5℃~0℃
- Meat Thaw Environment Temperature: -6℃~-3℃
- Material Input Way: Continuously
- Lubricating Way: Oil nozzle
- Thickness control: Manual Adjustment
- Control system: PLC, Waterproof Button, Frequency transformer

II Introduction:

- Driven by a motor; Controlled by the transducer.
- Push-button operation (low-speed/ medium-speed/ high-speed); Speed adjustable.

蔬菜切丁机 CD400



技术参数

- 电压：三相380v 频率50Hz
- 内筒直径：400mm
- 最大物料尺寸：直径小于200mm
- 外形尺寸：1440x1250x1600mm
- 整机材料：SUS304不锈钢
- 投料方式：连续
- 润滑方式：机体外油嘴
- 控制系统：防水按钮 变频器
- 总功率：7.5kW
- 产量：2000~4000kg/h
- 切割范围：3~12mm丁、丝、片
- 重量：600kg
- 冻肉切割温度范围：-5℃~0℃
- 生产解冻环境温度：-6℃~-3℃
- 厚度调节：人工手动

性能介绍

- 刀片采用进口刀片
刀片薄且锋利，切面光滑
- 清洗方式
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
根茎类蔬菜、水果和麻冻肉切丁、丝、片

Vegetable Dicer CD400

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customer's demands
- Power: 7.5kW
- Inner Drum Diameter: 400mm
- Capacity: 2000~4000kg/h
- Max Input Material Size: Diameter less than 200mm
- Cutting Size Range: 3~12mm Vegetables Slices, Strips and Cubes
- External Dimension: 1440*1250*1600mm
- Weight: 600kg
- Material of the Machine: SUS304 Stainless steel
- Cutting Temperature for the frozen meat: -5℃~0℃
- Meat Thaw Environment Temperature: -6℃~-3℃
- Material Input Way: Continuously
- Lubricating Way: Oil nozzle
- Thickness control: Manual Adjustment
- Control system: Waterproof Button, Frequency transformer

II Introduction:

- Use imported knife blades:
The knife pieces is thin and sharp, cutting surface is smooth
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Root vegetables slice, strips and cubes, Frozen Meat Slice, strips and Cubes

切菜机 CD190



技术参数

- 电压：三相380v 频率50Hz ● 功率：4.1Kw
- 外形尺寸：1800X1000X1500mm
- 重量：530kg
- 最大物料切割尺寸：宽190mm，高140mm
- 生产率：100-644刀/min
- 切割范围：1-50mm范围任意调整
- 进料口离地高度：910mm
- 出料口离地高度：520mm
- 整机材料：SUS304不锈钢 ● 切割方式：连续入料

性能介绍

- 输送带可徒手拆卸，方便清洁
- 上压料带前端随物料起伏，始终与切刀距离保持不变
- 安全保护：入料保护罩为感应开关，出料保护罩为霍尔开关
- 用途：叶类、根茎类蔬菜切段、切片

Vegetable Cutter CD190


Tech Data:

- Voltage&Frequency: 380V/50Hz/3phase or according to customer's demands
- Power: 4.1kw
- External Dimension: 1800*1000*1500mm
- Weight: 530kg
- Maximum cutting size: W190, H140mm
- Knife Cutting Speed: 100-644 times/minute
- Cutting Size: 1-50mm, according to customer's demands
- Input Material Height: 910mm
- Output Material Height: 520mm
- Machine Material: SUS304 Wire drawing Stainless steel
- Material Input Way: put the material continuously

II Introduction:

- The conveyor belt can be disassembled by hand for easy cleaning.
- The front end of the upper pressing belt fluctuates with the material, and the distance from the cutter remains unchanged
- Security protection: material input protective cover is an induction switch, and the material output protective cover is a hall switch
- Application: Leaf, root vegetables dicing and slicing

多功能切菜机 CD500-I



技术参数

- 电压：三相380v 频率50Hz
- 内筒直径：500mm
- 最大投入量：5kg/次
- 外形尺寸：1260x1000x1480mm
- 整机材料：SUS304镜面不锈钢
- 投料方式：连续
- 厚度调节：人工手动
- 总功率(Power)：2.25kW
- 产量：300~1000kg/h
- 切割范围：1~7mm 丝、片
- 重量：100kg
- 冻肉切割温度范围：-5℃~0℃
- 生产解冻环境温度：-4℃~-2℃
- 控制系统：防水按钮 变频器

性能介绍

- 最细丝切割1mm
- 切面光滑、薄厚均匀
- 清洗方式：用水枪直接清洗
- 安全装置：感应式自动电路切断
- 用途：土豆、胡萝卜等根茎类蔬菜和麻冻肉的切丝、切片

Multifunction Vegetable Shredding Machine CD500-I

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customers demands
- Power: 2.25kW
- Inner Drum Diameter: 500mm
- Capacity: 300~1000kg/h
- Max Input: 5kg/time
- Cutting Size Range: 1~7mm strips, slice
- External Dimension: 1260*1000*1480mm
- Weight: 100kg
- The Machine Material: SUS304 Mirror finished Stainless steel
- Cutting Temperature for the frozen meat: -5℃~0℃
- Meat Thaw Environment Temperature: -4℃~-2℃
- Input Way: Continuously
- Thickness Adjustment: Manual
- Control system: Waterproof button, frequency transformer

II Introduction:

- The finest strip cutting — 1mm
- Smooth cutting surface, thick even
- Cleaning Way: High pressure gun flush directly
- Safety Equipment: Inductive Automatic Shutoff Circuit
- Application: Potato, carrot etc root vegetables and frozen meat shredding and slicing.

切片切丝机 CDS



技术参数

- 电压：三相380v 频率50Hz
- 总功率：1.5 kW
- 产量：1000~3000kg/h
- 最大物料尺寸：直径260mm
- 切割厚度：1.5~7mm
- 外形尺寸：1000x1500x1650mm
- 重量：459 kg
- 整机材料：SUS304不锈钢

性能介绍

- 可将卷心菜、大白菜切丝；土豆、红薯根茎类蔬菜切片。
- 清洗方式：直接用水枪清洗

Vegetable Slicer CDS

Machine Parameters:

- Voltage: Three-Phase 380v
- Frequency: 50Hz
- Power: 1.5kW
- Maximum Material Size: diameter 260 mm
- Cutting Thickness: 1.5~7mm
- External Dimensions: 1000x1500x1650mm
- Weight: 459 kg
- Product Capability: 1000 ~ 3000kg/h
- Material of the Machine: SUS304 Stainless Steel

Machine Introduction:

- This machine can slice vegetables (potatoes, sweet potatoes, etc) and shred vegetables (cabbages and other root vegetables, etc)
- How to clean the machine: directly use water gun to clean

冻肉分块机 CDK455



技术参数

- 外形尺寸: 1960x990x1680mm
- 功率: 9kW
- 最宽物料尺寸: 440mm
- 重量: 1100kg
- 切割尺寸: 5~100mm范围任意调整
- 生产量: 15~45刀/min
- 控制系统: PLC 触摸屏 变频器
- 两把立切刀距离: 145mm
- 最高物料尺寸: 250mm
- 切割温度范围: -10℃~0℃
- 生产解冻环境温度: -8℃~-4℃
- 最佳切割温度: -6℃~-5℃

性能介绍

- 先进的切割方式: 六导柱直线运动切割机构
- 下刃口磨损可更换
- 清洗方式: 用水枪直接清洗
- 安全装置: 感应式自动电路切断
- 用途: 将大块原料肉分切成中小块物料 (可配合三维切丁机与绞肉机使用)

Frozen Meat Divider CDK455


I Technical Data:

- External dimension: 1960x990x1680 mm
- Power: 9kW
- Max input material width: 440mm
- Max input material height: 250mm
- Cutting temperature for the frozen meat: -10℃~0℃
- Best Cutting Temperature for the Frozen Meat: -6℃~-5℃
- Meat Thaw Environment Temperature: -8℃~-4℃
- Weight: 1100kg
- Cutting speed: 15~45 times/minutes
- Cutting size: 5~100mm or according to customer's demands
- Control system: PLC, Touch screen, Frequency transformer
- Distance between two vertical cutters: 145mm

II Introduction:

- Advanced cutting way: Six Guide Pillar Straight-line Cutting Structure
- The lower edge is worn and replaceable
- Cleaning Way: High pressure gun flush directly
- Safety Equipment: Inductive Automatic Shutoff Circuit
- Application: Cut the large material into small and medium pieces (this machine can be used with 3D Meat Dicer and Meat Mixer)

冻肉分块机 CDL455



技术参数

- 外形尺寸: 2450x1100x1660 mm
- 功率: 9kW
- 电压: 380V 频率50Hz
- 最宽物料尺寸: 440mm
- 最高物料尺寸: 250mm
- 切割温度范围: -10℃~0℃
- 生产解冻环境温度: -8℃~-4℃
- 最佳切割温度范围: -6℃~-5℃
- 切割尺寸: 5~100mm范围任意调整
- 重量: 1550kg
- 生产量: 15~45刀/min
- 切割尺寸: 5~100mm范围任意调整
- 控制系统: PLC 触摸屏 变频器 伺服
- 两把立切刀距离: 145mm

性能介绍

- 连续进料方式: 采用四套单独的上压料皮带与下压料皮带, 夹着物料向前输送, 上压料带与物料接触面始终保持平面压料状态
- 切割方式: 六导柱直线运动切割结构
- 下刀口磨损可更换
- 清洗方式: 用水枪直接清洗
- 安全装置: 感应式自动电路切断
- 用途: 将大块原料肉分切成中小块物料 (可配合三维切丁机与绞肉机使用)

Fresh Meat Slicer CD600

Tech Data:

- External dimension: 2450x1100x1660 mm
- Power: 9kW
- Voltage: 380V 50Hz
- Max input material width: 440mm
- Max input material height: 250mm
- Best cutting temperature for the frozen meat: -10℃~0℃
- Best production Thaw Ambient Temperature: -8℃~-4℃
- Best Cutting Temperature: -6℃~-5℃
- Weight: 1550kg
- Cutting speed: 15~45 times/minutes
- Cutting size: 5~100mm or according to customer's demands
- Control system: PLC, Touch screen, Frequency transformer
- Distance between two vertical cutters: 145mm

II Introduction:

- Advanced cutting way, four sets of separate upper and lower pressing belts are used to transport the material forward, and the contact surface between the upper pressing belt and the material is always in a flat pressing state.
- Cutting Way: Six Guide Pillar Straight-line Cutting Structure
- Knife Position Adjustable:
- When knife wear out, it could be adjusted downward
- Cleaning Way:
- High pressure gun flush directly
- Safety Equipment:
- Inductive Automatic Shutoff Circuit
- Application: Cut the large material into small and medium pieces (this machine can be used with 3D Meat Dicer and Meat Mixer)

冻肉切块机 CDQ200



技术参数

- 电压：三相380v 频率50Hz
- 产量：1000~2000kg/h
- 外形尺寸：1500x1235x1690mm
- 整机材料：SUS304不锈钢
- 投料方式：间歇
- 控制系统：防水按钮
- 总功率：11 kW
- 最大物料尺寸：600x500x190mm
- 重量：1000 kg
- 切割温度范围：-18℃~0℃
- 润滑方式：机体外油嘴

Frozen Meat Flaker CDQ200

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customer's demands
- Power: 11kW
- Capacity: 1000~2000Kg/h
- Max Input Material Size: 600*500*190mm
- External Dimension: 1500*1235*1690mm
- Weight: 1000kg
- Material of the Machine: SUS304 Stainless steel
- Cutting Temperature for the frozen meat: -18℃~0℃
- Intermittently
- Lubricating Way: Oil nozzle
- Control system: Waterproof Button


性能介绍

- 安全的上料斗
上料斗在切割或者放料时均与料仓形成封闭环境
- 机体面板倾斜
冲洗后可防止大量水滞留在机体表面
- 多位置料车进口
有前、右、后三个位置可以进出料车
- 清洗方式
用水枪直接清洗
- 安全装置
感应式自动电路切断
- 用途
冻肉切片

II Introduction:

- Safe loading hopper:
When loading and cutting, the space between loading hopper and cutting hopper is closed
- Machine structure with Angles of inclination:
There won't be much water stay on the machine after washing
- Skip Car Input directions:
Skip car could be put in from front, right and back three directions
- Cleaning Way:
High pressure gun flush directly
- Safety Equipment:
Inductive Automatic Shutoff Circuit
- Application:
Frozen Meat Slice

鲜肉切片机 CD600



✂ 技术参数

- 电压: 380v 频率50Hz
- 总功率: 2.2kW
- 切刀直径: 200mm 产量: 500kg/h
- 外形尺寸: 1540x900x1390mm
- 重量: 570kg
- 原料肉放入尺寸: ≤400mm
- 原料肉温: 冷鲜肉
- 切割尺寸: 3-50mm的丁、丝、片

⚙ 性能介绍

- 整机采用SUS304不锈钢制作, 保证了其耐用性和安全性, 并且易于清洗。本机有两个刀组料道, 可同时切割不同规格的两种尺寸的产品, 最小切割规格3mm, 可对宽度小于400mm, 厚度小于150mm的冷鲜肉进行肉片、肉丝的切割。
- 本机配备了进料传送带和进料保护罩, 在鲜肉切割时会起到很好的防护作用, 传送带传送速度62mm/s。
- 本机刀轴采用特种不锈钢, 强度高, 性能稳定不易弯曲变形。

Fresh Meat Slicer CD600


Tech Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customers' demands
- Power: 2.2kW
- Knife Diameter: 200mm
- Capacity: approx 500kg/h
- External Dimension: 1540*900*1390mm
- Weight: 570kg
- Raw Material Meat: Meat width ≤ 400 mm
- Temperature: Fresh Meat
- Dicing size: 3-50mm, Cubes, Shreds, slices

II Introduction:

- The whole machine is made of SUS304 stainless steel which makes the machine durable and safety, easy to clean.
- Two slicing sizes and two conveyor belts, CD600 could slice two different sizes at the same time.
- Minimum slicing size is 3mm, raw material fresh meat size width smaller than 400mm, thickness smaller than 150mm.
- CD600 equipped with Feed-in conveyor and protective cover, they all protect workers' safety. Conveyor belt speed is 62mm/s.
- Knife shaft adopts special stainless steel, high intensity, stable property and not easy to be out of shape.

拌馅机 CDF100/CDF350/CDF650/CDF1200



技术参数

- 电压：三相380v 频率50Hz
- 总功率：0.85/1.5kW, 2.2/3.3kW, 3/4.5kW, 5/7.5kW
- 转速：低速20r/min 高速40r/min
- 容积：100L, 350L, 650L, 1200L
- 外形尺寸：1020x620x1150mm, 1430x965x1590mm, 1700x1060x1710mm, 2300x1400x2200mm
- 重量：100kg, 400kg, 700kg, 1100kg,
- 整机材料：SUS304不锈钢
- 润滑方式：机体外油嘴
- 控制系统：防水按钮

Mixer CDF100/CDF250/CDF350/CDF650/CDF1200

I Technical Data:

- Voltage: 380V/50Hz/3phase or according to customer's demands
- Power: 0.85/1.5kW, 2.2/3.3kW, 3/4.5kW, 5/7.5kW
- Mixing Speed: Low Speed 20r/min, High Speed 40r/min
- Volume: 100L, 350L, 650L, 1200L
- External Dimension: 1020*620*1150mm, 1430*965*1590mm, 1700*1060*1710mm, 2300*1400*2200mm
- Weight: 100kg, 400kg, 700kg, 1100kg
- Machine Material: SUS304 Stainless steel
- Lubricating Way: Oil nozzle
- Control system: Waterproof Buttons


性能介绍

- 可徒手拆卸搅拌轴，不用任何工具。
- 大出料口
出料口大，出料速度快
- 方便的出料盖
出料盖可方便取下，以便于彻底清洗
- 食品安全可靠
传动部分与箱体完全隔离，保证馅料卫生安全
- 清洗方式
用水枪直接清洗
- 用途
用于饺子、火腿等馅料的搅拌

II Introduction:

- No need any tools, workers could remove the mixing shaft only by hands
- Big Output:
The output is very big, output speed is quite fast
- Convenient Output Cover:
The output cover is very easy to remove, it's convenient for washing completely
- Guarantee of Food safety:
Driving part is separated completely with the mixing tank, guarantee the food safety
- Cleaning Way:
High pressure gun flush directly
- Application:
Mixing stuffing for dumplings or sausages

全自动洗菜机 CD750





技术参数

- 电压：三相380v 频率50Hz
- 总功率：17.1kW
- 水箱容积：740L
- 缸体容积：1300L
- 产量：700~1000kg/h
- 过滤间隙：0.6mm
- 外形尺寸：9040x1890x1750mm
- 重量：900kg
- 整机材料：SUS304不锈钢
- 清洗方式：连续
- 控制系统：防水按钮

性能介绍

- 一体式振筛
结构稳定，不易损坏
- 巧妙的转笼结构
徒手可将过滤转笼拆下，然后进行清洗或者更换。
- 清洗方式
用水枪直接清洗
- 用途
用于联机清洗蔬菜原料或者切割好的产品

Automatic Vegetable Washing Line CD750

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customer's demands
- Power: 17.1kW
- Water Tank Volume: 740L
- Cylinder Tank: 1300L
- Capacity: 700~1000kg/h
- Time of Filtration: 0.6mm
- External Dimension: 9040*1890*1750mm
- Weight: 900kg
- Material of the Machine: SUS304 Stainless steel
- Washing Way: Continuously
- Control system: Waterproof Buttons

II Introduction:

- One-piece Vibrating Screen:
Stable structure, not easy to break down
- Smart Rotating Drum structure:
Rotating drum could be removed by hands, easy to wash or change.
- Cleaning Way:
High pressure gun flush directly
- Application:
Vegetables or products after cutting, the machine connect together will be a washing line.



万能洗菜机 CD1000



✎ 技术参数

- 电压：三相380v 频率50Hz
- 总功率：2.25kW
- 容积：546L
- 产量：30~50kg/次
- 外形尺寸：1800x1040x1330mm
- 重量：350kg
- 整机材料：SUS304不锈钢
- 控制系统：防水按钮

⚙️ 性能介绍

- 翻斗控制
液压驱动控制，噪音低
- 清洗方式
用水枪直接清洗
- 用途
用于清洗各种蔬菜水果

Vegetable Washing Machine CD1000

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customer's demands
- Power: 2.25kW
- Volume: 546L
- Capacity: 30~50kg/h
- External Dimension: 1800*1040*1330mm
- Weight: 350kg
- Material of the Machine: SUS304 Stainless steel
- Control system: Waterproof Buttons

II Introduction:

- Dump Control:
Hydraulic control, low noise, turn over degree 110°C
- Cleaning Way:
High pressure gun flush directly
- Application:
Vegetables and fruits washing

去根机 CDG



技术参数

- 电压：三相380v 频率50Hz
- 总功率：0.55kW
- 产量：5-10秒/棵
- 气压：0.6MPa
- 外形尺寸：865x820x1405mm
- 重量：234 kg
- 整机材料：SUS304不锈钢

性能介绍

- 专用于白菜，圆白菜去根
- 产品高效，双手操作，安全、方便、稳定、卫生
- 自由调节圆白菜（白菜）去根深度
- 多种去根刀具，可以控制去根大小
- 清洗方式：直接用水枪清洗

Vegetable Root Remover CDG

Machine Parameters:

- Voltage: Three-Phase 380v
- Frequency: 50Hz
- Power: 0.55kW
- Air Pressure: 0.6MPa
- External Dimensions: 865x820x1405mm
- Weight: 234 kg
- Production Capability: 5-10 pieces/sec
- Material of the Machine: SUS304 Stainless Steel

Machine Introduction:

- Professional in cabbage and other vegetables root removing
- The machine is easy to use (can operate with hands directly), and the machine is efficient, convenience and stable.
- The machine can use customized blade size to meet different vegetable root use.
- How to clean the machine: directly use water gun to clean.

土豆去皮机 CD50/CD100



技术参数

- 电压：三相380v 频率50Hz
- 总功率：1.5kW, 2.2kW
- 产量：50kg/4分钟, 100kg/4分钟
- 外形尺寸：660x850x690 mm, 1800x1300x860mm
- 重量：300kg, 420kg
- 整机材料：SUS304不锈钢
- 润滑方式：机体油嘴
- 控制系统：防水按钮

性能介绍

- 先进的毛辊更换结构
用简单工具对使用不同程度的毛辊进行调位或更换
- 清洗方式
用水枪直接清洗
- 喷水装置
防护盖自带四周圈喷水装置
- 用途
土豆、胡萝卜等根茎类的去皮清洗和猪手等

Potato Peeler CD50/CD100

I Technical Data:

- Voltage&Frequency: 380V/50Hz/3Phase or according to customers' demands
- Type: CD50, CD100
- Power: 1.5kW, 2.2kW
- Capacity: 50kg/4Minutes, 100kg/4Minutes
- External Dimension: 1660*850*690mm, 1800*1300*860mm
- Weight: 300kg, 420kg
- Machine Material: SUS304 Stainless steel
- Lubricating Way: Oil nozzle
- Control system: Waterproof Button

II Introduction:

- Advanced brush roller changing structure:
With simple tools, brush rollers could be changed to other position or removed
- Cleaning Way:
High pressure gun flush directly
- Water-spray equipment:
There is water-spray on the cover
- Application:
Potato, carrots etc root vegetables washing and peeling, and Pig feet etc washing

输送机 CDZ-44



技术参数

- 外形尺寸: 2650x717x1956 mm
- 功率: 1.1kW
- 输送料道宽: 284mm
- 带速: 270mm/s
- 重量: 320kg

性能介绍

- 本机主要用来衔接前后工序环节或设备;
- 由单独一台电机驱动, 可加装变频器实现调速控制;
- 本机结构采用单悬臂式架体结构, 传送带拆卸更换清洗方便;
- 传送带上带有分隔板, 可输送球形等状产品;
- 整体形状为Z字形结构, 接料和进料不易漏料。

Conveyor CD30-Z

Machine Parameters:

- External Dimensions: 2650x717x1956mm
- Power: 1.1kW
- Width of the Input Material Belt: 284mm
- Speed: 270mm/s
- Weight: 320kg

Machine Introduction:

- the machine is mainly used to connect the front and back food processing link and equipment
- Driven by a single motor, a frequency converter can be added to realize speed control
- The machine is a single cantilever frame structure, and the conveyor belt is easy to disassemble, replace and clean;
- There are dividers on the conveyor belt, which can transport spherical and other products.
- The overall shape is a zigzag structure, and the material is not easy to leak when receiving and feeding.



www.cdqgjx.com

河北川达机械制造有限公司

Add : 河北省唐山市玉田县鸦鸿桥镇穆庄子工业园区

Add : Muzhuangzi Industrial Park, Yahongqiao Town, Yutian County, Tangshan City, Hebei Province.

PC : 064102

Tel : 13933058487 18686773488

Web : www.cdqgjx.com

E-mail : cd@cdqgjx.com