


HIGH QUALITY
MADE IN GERMANY



SEALED!

RUBBER-STEEL-GASKETS

G-ST-FLAT GASKETS
G-ST PROFILE GASKETS
G-ST WEDGE RINGS






RUBBER-STEEL FLANGE GASKETS

PRODUCT RANGE



NEW DEVELOPMENTS

NBR DUO EL Aramid Gasket
G-ST-P / KN PP
G-ST-P / HYBRID




Page 12 - 13



G-ST

For various applications




Page 14 - 15



G-ST/GUSS

In special dimensions, to completely cover the flange face




Page 16



G-ST-P/S

For various applications, top choice for joints connecting non-metallic (plastic or GRP) and steel flanges




Page 17 - 22



G-ST-P/K

Ideal for flange connections from pairs of plastic stub ends




Page 23 - 24



G-ST-P/KN

Universally applicable, ideal for partially coated flanges and extreme load




Page 25 - 28



G-ST-P/HTB

For steel flange connections with high thermal load capacity




Page 29



G-ST-P/OE

Customized dimensions with a visible stainless steel insert



Page 30



G-ST-Wedge Ring

Continuously adjustable from 0 to 8 degrees. Safe and easy solution for alignment problems



Page 31

SPECIAL GASKETS


PRODUCT RANGE

You can obtain an individual data sheet for the following assortments



G-ST/FD

Flat version of the proven G-ST gasket type, thickness 3 mm




BFD-Flange Gaskets

For risers in well construction to protect the coated pipe




G-ST-P/GR

Profile gasket for rubberized pipelines following guideline FDG 0389 for flanges according to DIN 28034




G-ST-P/ISO

Gasket sets for galvanic separation of different metallic flange materials




Camprofile Gasket

For high pressures in gas and steam application



RTJ Ring Joint Gaskets

For highest pressures in the gas applications



PTFE-Gaskets

With perforated steel insert for sealing of chemically aggressive media



RUBBER-STEEL-FLANGE-GASKETS PROVEN IN PIPELINE CONSTRUCTION



G - ST - P / *	
S	Steel flange connections
K	Plastic flange connections
KN	Force shunt
OE	Open insert
HTB	High thermal load capacity
P	Profile
ST	Steel
G	Rubber

Rubber-steel-flange-gaskets and adjustable wedge rings have proven their worth for decades in all areas of plant and pipeline construction. Well-known companies in the primary industry, the chemical industry and last but not least countless utility companies at home and abroad appreciate the advantages of KROLL & ZILLER sealing elements.

Over 80 years of experience in solving **individual sealing problems** means that our customers have a range of flange gaskets with immense operational reliability. They benefit from these advantages when using Kroll & Ziller gaskets:

- + A high degree of cost-effectiveness through a reduction in operating costs
- + An environmentally compatible material flow by avoiding leakages

Growing international competition is forcing cost minimization in all operational areas. Production disruptions, the occurrence of rejects, maintenance and servicing costs must be avoided by selecting optimum components. The dangers of possible environmental pollution must be to be excluded. KROLL & ZILLER continuously pursues a policy of specialization, research and technical development in close cooperation with an international clientele.

The large available range of gaskets offers the possibility of high quality standardization. A **high level of economy** (reduced stock) is coupled with **excellent handling**. The latter is characterized by the stabilizing steel core, which considerably simplifies assembly, especially for large nominal diameters.



OUR GASKETS YOUR ADVANTAGES

- + Tightness at low surface pressure and at low tightening torques
- + Very good adaptability to the sealing surfaces
- + Low leakage rates thanks to homogeneous structure of elastomer materials
- + Blow-out resistance and maximum stability due to centrally positioned, corrosion-protected and vulcanized steel insert
- + Optimum handling when installing the gasket

RUBBER-STEEL-FLANGE-GASKETS QUALITY "MADE IN GERMANY"



Quality "Made in Germany"

Our products are 100 % "Made in Germany", making our supply chains stable and reliable at all times. With more than 80 years of experience in solving individual requirements, KROLL & ZILLER is your international and reliable partner for gaskets with highest operational safety.

Research and development in Germany

Our technological aspirations are preceded by research and development at our site in Germany in order to continue to drive innovation in the future. With our certification according to DIN EN ISO 9001:2015 we ensure that the principles of quality management are successfully implemented and that our development processes are continuously improved.



Optimal delivery capacity

A large and well-stocked warehouse is the guarantor for a rapid ability to deliver. The logistics department with its own carpenter's workshop packs and ships our gaskets all over the world.

RUBBER-STEEL-FLANGE-GASKETS MATERIALS



NR	= Natural rubber Temp.tmax. -30 ...+60° C, Shore-A-Hardness 65 ± 5
NBR-DUO-EL	= Acrylonitrile-Butadiene Rubber. Temp. tmax.-25...+70°C, Shore-A-Hardness 80 ± 5 <i>DRINKING WATER according to DIN-EN 681-1 + GAS according to DIN-EN 682</i> Certificates / Approval according to valid standards and regulations
HNBR	= Hydro-generated-Acrylonitrile-Butadiene Rubber Temp.tmax. -25 ...+150° C, Shore-A-Hardness 75 ± 5
CR	= Chloroprene Rubber Temp.tmax. -25 ...+95° C, Shore-A-Hardness 60 ± 5
CSM	= Chloro-sulfonyl-polyethylene rubber Temp. tmax.-20...+120°C, Shore-A-Hardness 80 ± 5
EPDM(S)	= Ethylene Propylene Diene Monomer Rubber Crosslinking Agent Sulfur Temp.tmax.-30...+120°C; Shore-A-Hardness 75 ± 5
EPDM-PW(P)	= Ethylene-Propylene-Diene-Monomer-Rubber Temp.tmax.-30...+120°C; Shore-A-Hardness 70 ± 5
EPDM-EL	= Ethylene Propylene Diene Monomer Rubber Crosslinking Agent Sulfur Temp.tmax.-30...+120°C; Shore-A-Hardness 75 ± 5 With certification for drinking water according to DIN-EN-681-1, as well as further requirements in the automotive industry up to power plant and air conditioning technology
FKM	= Fluorinated Rubber Temp.tmax.-20...+ 200°C; Shore-A-Hardness 80 ± 5
Steel insert	1.0330, other materials on request

AREAS OF APPLICATION

TIGHT IN EVERY APPLICATION

Gaskets from KROLL & ZILLER have proven themselves for decades in all areas of pipeline and plant construction.

THE AREAS OF APPLICATION:



Drinking water



Natural gas



Chemical & Petrochemical




Fire protection



GRP & Plastic



Food Technology



Apparatus & tank construction




Mining



Hydrogen



20571 DIN EN 10222-2 P1.0535 73.08.17 2105 115 Made in Germany



G-ST-FLANGE-GASKETS

PROVEN IN PIPELINE AND PLANT CONSTRUCTION

Rubber-steel-flange-gaskets from KROLL & ZILLER are used for the safe sealing of flange connections in all fields. The use of rubber-steel gaskets is particularly recommended in areas of application where a secure gasket is required with low surface pressure:

Reliable sealing

Reliable sealing of flanged joints on pipelines has become possible thanks to the development of KROLL & ZILLER G-ST gaskets. During the process of vulcanization, extreme adhesion is achieved between the steel insert and the rubber coating. Even under the highest stresses, this makes displacement, detachment or even blow-out virtually impossible.

No flow losses

The standard-compliant dimensioning prevents unnecessary flow losses in the case of cross-sectional overlap. This is combined with optimum handling during installation, as the gasket is centered on the bolt ring and has highdimensional stability due to the steel insert.

KROLL & ZILLER NEW DEVELOPMENTS



HIGH QUALITY
MADE IN GERMANY

NEW

NEW AT KROLL & ZILLER

NBR DUO EL ARAMID GASKET

Non asbestos gasket (1500 x 1500 x 2 mm)


- + Universally applicable gasket with very good mechanical, thermal and chemical resistance
- + Dimensions (d1 x d2 x s1) in accordance with: DIN EN 1514-1 / DIN 2690 / ASME B16.21 / Special dimension
- + Gaskets characteristics according to DIN EN 13555
- + Applicable in various fields such as chemical and petrochemical, drinking water, gas, food industry and many more

Application limits:

- + Pressure application limits: 100 bar
- + Temperature limits: 200 °C (Continuous) / 350 °C (Peak)

Approvals:

- + TA-Luft
- + Potable Water (W270, EL, WRAS)
- + DIN 3535-6 (DVGW, SVGW)
- + DIN 30653, 1 bar (former VP401)
- + EC 1935/2004 (Food certification)
- + BAM (Oxygen)
- + ABS (American Bureau of Shipping)
- + AGA AS Class III, RWP 2,0 kPa, Temp. -10 °C bis +135 °C
- + DNV GL (Piping in shipbuilding certification)



KROLL & ZILLER NEW DEVELOPMENTS

RUBBER-STEEL-GASKET G-ST-P / KN PP

Dimensions ($d_1 \times d_4 \times s_1/s_2$) in accordance with: DIN EN 1514-1 / DIN 2690 / ASME B16.21

- + Gasket with polypropylene thrust ring (available as a full face and IBC version)
- + Designed for application in GRP and plastic flange connections
- + By distributing the contact pressure over a small sealing area, optimum system tightness can be achieved even at low tightening torques
- + The plastic thrust ring protects the flange surface and prevents overpressing of the sealing element and bending of the flange

Application limits:

- + Pressure application limits: Nominal size-related for operating pressures up to 100 bar
- + Temperature limits: Depending on (rubber) material

Approvals:

- + Potable water certification: EPDM-EL, NBR-DUO-EL (From DN400 EPDM with ACS certification)
- + FDA certification: EPDM, NBR-DUO-EL



Gasket characteristics:

- + Wide range of materials for high pressures (up to 100 bar) and pressure load changes (force shunt gasket)
- + Different rubber materials available
DN15 - DN400: NR, NBR, HNBR, EPDM, CR, CSM, Silicon
DN450 - DN4000 (+): NBR, EPDM, FKM, Silicon
- + Available as Full Face (FF) and IBC version
- + Available in different plastic materials (PP, PE etc.)

RUBBER-STEEL GASKET G-ST-P / HYBRID

Dimensions ($d_1 \times d_4 \times s_1/s_2$) in accordance with: DIN EN 1514-1 / DIN 2690 / ASME B16.21

- + Universal hybrid gasket which combines the advantages of a rubber steel gasket with a non-asbestos gasket
- + Reliable sealing performance due to the internal rubber profile even with low tightening torques
- + The non-asbestos gasket absorbs large forces and acts as a second sealing barrier
- + Customized dimensions possible

Application limits:

- + Temperature limits: up to 220 °C / 428 °F depending on (rubber) material
- + Pressure application limits: Nominal size-related on operating pressure up to 100 bar


Approvals:

- + TA-Luft
- + Potable Water (W270, EL, WRAS)
- + DIN 3535-6 (DVGW, SVGW)
- + DIN 30653, 1 bar (former VP401)
- + EC 1935/2004 (Food certification)
- + BAM (Oxygen)
- + ABS (American Bureau of Shipping)
- + AGA AS Class III, RWP 2,0 kPa, Temp. -10 °C bis +135 °C
- + DNV GL (Piping in shipbuilding certification)



Gasket characteristics:

- + Wide range of materials for high pressures (up to 100 bar) and pressure load changes
- + Different rubber materials available
DN15 - DN400: NR, NBR, HNBR, EPDM, CR, CSM, Silicone
DN450 - DN4000 (+): NBR, EPDM, FKM, Silicon
- + Different non-asbestos gasket materials available
- + Also available as Full Face (FF) version




G-ST

Gaskets for pipeline constructions

G-ST similar EN 1514-1

Diameter Nominal	Nominal pressure	Dimensions in mm					
		d ₁	x	d ₂	x	s ₁	
15	10-40	22	x	51	x	4	
20	10-40	27	x	61	x	4	
25	10-40	34	x	71	x	4	
32	10-40	43	x	82	x	4	
40	10-40	49	x	92	x	4	
50	10-40	61	x	107	x	4	
65	10-40	77	x	127	x	4	
80	10-40	89	x	142	x	4	
100	6	115	x	152	x	5	
100	10-16	115	x	162	x	5	
100	25-40	115	x	168	x	5	
125	10-16	141	x	192	x	5	
125	25-40	141	x	194	x	5	
150	10-16	169	x	218	x	5	
150	25-40	169	x	224	x	5	
200	10-16	220	x	273	x	6	
200	25	220	x	284	x	6	
200	40	220	x	290	x	6	
250	10	273	x	328	x	6	
250	16	273	x	329	x	6	
250	25	273	x	340	x	6	
250	40	273	x	352	x	6	
300	6	324	x	373	x	6	
300	10	324	x	378	x	6	
300	16	324	x	384	x	6	
300	25	324	x	400	x	6	
300	40	324	x	417	x	6	
350	10	356	x	438	x	7	
400	10	407	x	489	x	7	
400	16	407	x	495	x	7	
400	25	407	x	514	x	7	
• 400	40	407	x	546	x	7	
500	10	508	x	594	x	7	
500	40	508	x	628	x	7	
600	10	610	x	695	x	7	
700	10	712	x	810	x	8	
800	10	813	x	917	x	8	
1000	10	1016	x	1124	x	8	
1200	2,5	1220	x	1290	x	8	
1200	6	1220	x	1307	x	8	
1200	10	1220	x	1341	x	8	
1200	16	1220	x	1342	x	8	
1600	2,5	1620	x	1700	x	8	
1600	10	1620	x	1772	x	8	
1800	10	1820	x	1972	x	8	
2000	10	2020	x	2182	x	8	

• Available on request




G-ST similar DIN 2690

Diameter Nominal	Nominal pressure	Dimensions in mm					
		d ₁	x	d ₂	x	s ₁	
50	10-40	57	x	107	x	4	
100	10-16	108	x	162	x	5	
100	25-40	108	x	167	x	5	
125	6	141	x	182	x	5	
125	10-16	133	x	192	x	5	
150	6	169	x	207	x	5	
150	10-16	159	x	218	x	5	
175	10-16	195	x	248	x	5	
175	40	195	x	267	x	5	
200	10-16	216	x	273	x	6	
200	25	216	x	285	x	6	
250	10	267	x	328	x	6	
300	10	318	x	378	x	6	
350	6	368	x	423	x	7	
350	10	368	x	438	x	7	
350	16	368	x	445	x	7	
350	25	368	x	458	x	7	
350	40	368	x	475	x	7	
400	6	420	x	473	x	7	
400	10	420	x	490	x	7	
400	16	420	x	497	x	7	
400	25	420	x	515	x	7	
400	40	420	x	547	x	7	
450	10	470	x	540	x	7	
500	6	520	x	575	x	7	
500	10	520	x	595	x	7	
500	16	520	x	618	x	7	
500	25	520	x	625	x	7	
600	10	620	x	695	x	7	
600	16	620	x	735	x	7	
600	25	620	x	730	x	7	
600	40	620	x	745	x	7	
700	6	720	x	785	x	8	
700	10	720	x	810	x	8	
800	6	820	x	890	x	8	
800	10	820	x	915	x	8	
800	16	820	x	910	x	8	
800	25	820	x	940	x	8	
900	6	920	x	990	x	8	
900	10	920	x	1015	x	8	
900	16	920	x	1010	x	8	
900	25	920	x	1040	x	8	
1000	6	1020	x	1090	x	8	
1000	10	1020	x	1120	x	8	
1000	16	1020	x	1125	x	8	
1000	25	1020	x	1150	x	8	
1000	40	1020	x	1190	x	8	
1100	16	1120	x	1225	x	8	
1100	25	1120	x	1260	x	8	
1200	25	1220	x	1360	x	8	
1200	40	1220	x	1395	x	8	
1300		1320	x	1435	x	8	
1400	10	1420	x	1545	x	8	
1500		1520	x	1645	x	8	

G-ST SPECIAL DIMENSIONS

G-ST (Special dimension)



Diameter Nominal	Dimensions in mm				
DN	d ₁	x	d ₂	x	s ₁
15	15	x	54	x	3
20	23	x	54	x	3
20	23	x	60	x	3
25	28	x	43	x	3
25	28	x	53	x	3
25	28	x	65	x	3
25	30	x	48	x	4
25	30	x	71	x	4
25	33	x	70	x	3
25	36	x	50	x	5
32	38	x	82	x	4
40	43	x	55	x	3
40	45	x	85	x	4
40	45	x	92	x	4
40	45	x	102	x	4
50	50	x	100	x	8
50	52	x	70	x	3
50	52	x	78	x	3
50	55	x	69	x	3
50	55	x	112	x	4
50	57	x	87	x	3
50	57	x	95	x	4
50	57	x	118	x	3
50	62	x	118	x	3
50	63	x	75	x	4
65	65	x	85	x	4
65	70	x	107	x	4
65	71	x	91	x	3
65	71	x	137	x	4
80	80	x	104	x	3
80	80	x	118	x	3
80	85	x	147	x	5
80	87	x	105	x	3
80	92	x	124	x	3
80	95	x	121	x	4
100	100	x	148	x	5
100	102	x	138	x	3
100	105	x	127	x	4
100	108	x	149	x	4
100	108	x	173	x	5
100	110	x	150	x	4
100	110	x	160	x	10
100	115	x	149	x	4
100	116	x	218	x	5
100	120	x	170	x	5
100	125	x	170	x	4
125	125	x	172	x	5
125	130	x	151	x	4
125	132	x	175	x	5
125	133	x	210	x	5
125	150	x	208	x	5
150	150	x	210	x	5
150	150	x	212	x	5
150	152	x	177	x	5
150	152	x	194	x	3
150	152	x	210	x	3,5
150	154	x	258	x	5

Diameter Nominal	Dimensions in mm				
DN	d ₁	x	d ₂	x	s ₁
150	156	x	177	x	4
150	158	x	188	x	4
150	159	x	203	x	5
150	160	x	215	x	3,5
150	160	x	247	x	5
150	169	x	203	x	5
150	170	x	195	x	5
150	170	x	285	x	5
150	175	x	228	x	5
175	180	x	240	x	5
175	187	x	238	x	6
175	192	x	228	x	4
190	192	x	277	x	5
190	203	x	239	x	5
200	203	x	273	x	6
200	204	x	305	x	6
200	205	x	270	x	5
200	208	x	242	x	5
200	210	x	258	x	6
200	215	x	270	x	4
200	220	x	259	x	5
200	220	x	309	x	6
200	225	x	239	x	5
225	225	x	280	x	5
225	230	x	267	x	5
250	255	x	295	x	4
250	255	x	312	x	5
250	267	x	342	x	6
250	274	x	364	x	6
300	300	x	345	x	6
300	300	x	349	x	6
300	300	x	365	x	6
300	300	x	378	x	5
300	307	x	353	x	5
300	310	x	358	x	8
300	310	x	363	x	5
350	344	x	403	x	6
350	350	x	410	x	7
350	350	x	435	x	7
350	370	x	450	x	5
400	400	x	490	x	6
400	400	x	455	x	5
400	420	x	470	x	6
450	470	x	570	x	7
450	480	x	574	x	7
450	485	x	535	x	7
450	490	x	540	x	5
500	500	x	580	x	7
500	504	x	542	x	7
500	508	x	585	x	7
500	520	x	585	x	6
500	552	x	625	x	6
550	595	x	643	x	6
600	620	x	710	x	7
600	622	x	674	x	7
650	650	x	710	x	8
650	676	x	736	x	8

Diameter Nominal	Dimensions in mm				
DN	d ₁	x	d ₂	x	s ₁
650	650	x	810	x	8
700	704	x	746	x	8
700	720	x	895	x	8
800	800	x	840	x	8
950	982	x	1050	x	8

G-ST (Special dimension)

In special dimensions, for PN 10
Outside diameter similar to DIN 2690, with
deviating inner diameter

Diameter Nominal	Dimensions in mm				
DN	d ₁	x	d ₂	x	s ₁
25	17	x	70	x	4
40	34	x	92	x	4
50	44	x	107	x	4
65	61	x	127	x	4
80	72	x	142	x	4
100	97	x	162	x	5
125	121	x	192	x	5
150	149	x	218	x	5
200	196	x	273	x	6
250	250	x	328	x	6
300	299	x	378	x	7
350	329	x	438	x	7
400	378	x	490	x	7
500	485	x	595	x	7
600	587	x	695	x	7
700	687	x	810	x	8
800	786	x	915	x	8
900	884	x	1015	x	8
1000	986	x	1120	x	8

G-ST-FLAT-GASKETS

G-ST / GUSS



source: LWG - Cottbus

The right gasket for the utility industry

Flat gaskets for flanged joints in pipeline and plant construction have historically been manufactured according to standards or guidelines that specified precise dimensions for inside and outside diameters. The inside diameters are generally so large that a considerable area of the sealing strip of the flange is not covered.

Example:

FPG ductile iron pipe with cast-on standard flanges lined with cement mortar, DN 80, PN 10-25

$$d_{i_{\text{Pipe}}} = 78 \text{ mm}$$

$$d_{a_{\text{Sealing strip flange}}} = 133 \text{ mm sealing surface} = 9.115 \text{ mm}^2$$

Flat gasket DN 80, PN 10-40 according to DIN EN 1514-1

$$d_i = 89 \text{ mm} \quad d_a = 142 \text{ mm}$$

$$\text{Sealing surface with } d_{a_{\text{Sealing strip flange}}} = 7.672 \text{ mm}^2$$


It shows: approx. 16 % of the sealing surface is not covered!

As the corrosion protection is often insufficient in particular in older equipment parts, hence an increased rust nodule formation is caused especially with aggressive water qualities. When using the KROLL & ZILLER gasket Type **G-ST/GUSS** this problem is consequently eliminated!

The inner diameters are based on the nominal diameters of common pipes and fittings: Of course, no other restrictions are associated with a conversion.

G-ST / GUSS

Diameter Nominal	Nominal pressure	Dimensions in mm				
DN	PN	d_1	x	d_2	x	s_1
40	10-40	40	x	91	x	4
50	10-40	50	x	106	x	4
60	10-40	60	x	117	x	4
65	10-40	65	x	126	x	4
80	10-40	80	x	142	x	4
100	10-16	100	x	162	x	5
125	10-16	125	x	192	x	5
150	10-16	150	x	218	x	5
200	10-16	200	x	273	x	6
250	10-16	250	x	328	x	6
300	10	300	x	378	x	7
300	16	300	x	384	x	7
350	16	350	x	444	x	7
400	10	400	x	490	x	7
400	16	400	x	495	x	7
500	10	500	x	594	x	7
500	16	500	x	617	x	7



G-ST-PROFILE GASKETS THE NEW GENERATION

For KROLL & ZILLER, technological progress is embodied in the G-ST-P profile gasket program. A graphic representation of the seal cross-section makes the basic idea clear. The spherical G-ST basic body is combined with an "O-ring". The toroidal sealing ring, as the optimum static sealing element, performs almost impossible tasks even without cost-intensive torquing on the flange.

The **G-ST-P** profile gasket combines the advantages of the individual elements. High surface pressures transmitted in the main flow of force are absorbed by the stiff spherical G-ST gasket. The corrosion-protected vulcanized-in flat steel ring can easily withstand the required test pressure. The round sealing ring, which is located in the power bypass, fits snugly against the sealing surfaces, even at low surface pressures. Uneven surfaces and grooves, even slight misalignments, are compensated for. In addition to the material-saving assembly with small necessary tightening torques, a previously unattained operational reliability is realized.

Once inserted - SEALED!

These advantages take on special weight in flange connections of thermoplastic pipes (materials: PVC, PE, PP, PVDF). The special gasket KROLL & ZILLER **G-ST-P/K** (K stands for plastic flange joints) has as a special feature a wider sealing surface and a rectangular instead of spherical cross-section next to the "O-ring" which prevents the bending of the flange or the fixed flange is prevented from bending up. The toroidal sealing ring reliably fills the enlarged gap and low necessary tightening torques protect against overloading of the fasteners.





G-ST-PROFILE GASKETS

ELASTOMER AND INSERT MATERIAL FREELY SELECTABLE

Advantages in usage:

- + Tight at low tightening torques
- + Compensation of surface defects
- + Flange and bolts can be designed lighter
- + Lifetime of plastic flange connections is significantly higher (consideration of the creep behavior)
- + Angular deviations can be compensated more easily compared to simple flat gaskets
- + Expensive grooving for round cord ring groove or offset grooving on the flange can be omitted



G-ST-PROFILE GASKETS HOLDS TIGHT

The progress in the KROLL & ZILLER sealing program is proven in the factory test.




Test parameters

Medium: Water
Temperature: 20° C
Test pressure: constant, 10 bar
Test objects: DN 500, according to DIN 2690

- a = Rubber flange gasket with textile inlay NBR
 b = G-ST-Flat Gasket NBR
 c = G-ST-P/S-Profile Gasket NBR


The diagram shows the qualitative result of the test series.
 At a constant pressure, the G-ST-P/S profile gasket requires only a fraction of the determined necessary tightening torque of a G-ST flat gasket.

Nevertheless, the recommendation is to carry out the assembly with the higher value of the G-ST gasket. The plus in safety compensates for many imponderables in practice.



G-ST-P/S

DIVERSE RANGE OF APPLICATIONS



G-ST-P/S based on EN 1514-1

Diameter Nominal	Nominal pressure	Dimensions in mm				
DN	PN	d ₁	x	d ₂	x	s ₁ /s ₂
15	10-40	22	x	51	x	3/4
20	6	27	x	64	x	3/4
20	10-40	27	x	61	x	3/4
25	10-40	34	x	71	x	3/4
32	6	43	x	76	x	3/4
32	10-40	43	x	82	x	3/4
40	10-40	49	x	92	x	4/5
50	6	61	x	96	x	4/5
50	10-40	61	x	107	x	4/5
65	6	77	x	116	x	4/5
65	10-40	77	x	127	x	4/5
80	10-40	89	x	142	x	4/5
100	6	115	x	152	x	5/6
100	10-16	115	x	162	x	5/6
100	25-40	115	x	168	x	5/6
125	6	141	x	182	x	5/6
125	10-16	141	x	192	x	5/6
125	25-40	141	x	194	x	5/6
150	6	169	x	207	x	6/8
150	10-16	169	x	218	x	6/8
150	25-40	169	x	224	x	6/8
200	6	220	x	262	x	6/8
200	10-16	220	x	273	x	6/8
200	25	220	x	284	x	6/8
200	40	220	x	290	x	6/8
250	6	273	x	317	x	6/8
250	10	273	x	328	x	6/8
250	16	273	x	329	x	6/8
250	25	273	x	340	x	6/8
250	40	273	x	352	x	6/8
300	6	324	x	373	x	6/8
300	10	324	x	378	x	6/8
300	16	324	x	384	X	6/8
300	25	324	x	400	x	6/8
300	40	324	x	417	x	6/8
350	10	356	x	438	x	7/10
350	16	356	x	444	x	7/10
400	10	407	x	489	x	7/10
400	16	407	x	495	x	7/10
450	10	458	x	539	X	7/10
• 450	16	458	x	555	X	7/10
500	10	508	x	594	X	7/10
500	16	508	x	617	X	7/10
600	10	610	x	695	X	7/10
• 600	16	610	x	734	X	7/10
700	10	712	x	810	X	8/11
• 700	16	712	x	804	X	8/11
800	10	813	x	917	X	8/11
• 800	16	813	x	911	X	8/11
900	10	915	x	1017	X	8/11
• 900	16	915	x	1011	X	8/11
1000	10	1016	x	1124	X	8/11
• 1000	16	1016	x	1128	X	8/11
1200	2,5	1220	x	1290	x	8/11
1200	6	1220	x	1307	x	8/11
1200	10	1220	x	1341	x	8/11
1200	16	1220	x	1342	x	8/11
1400	2,5	1420	x	1490	x	8/11

G-ST-P/S based on DIN 2690

Diameter Nominal	Nominal pressure	Dimensions in mm				
DN	PN	d ₁	x	d ₂	x	s ₁ /s ₂
350	6	368	x	423	x	7/10
350	10	368	x	438	x	7/10
350	16	368	x	445	x	7/10
350	25	368	x	458	x	7/10
350	40	368	x	475	x	7/10
400	6	420	x	473	x	7/10
400	10	420	x	490	x	7/10
400	16	420	x	497	x	7/10
400	25	420	x	515	x	7/10
400	40	420	x	547	x	7/10
450	6	470	x	528	x	7/10
450	10	470	x	540	x	7/10
450	16	470	x	557	x	7/10
450	25	470	x	565	x	7/10
450	40	470	x	572	x	7/10
500	6	520	x	578	x	7/10
500	10	520	x	595	x	7/10
500	16	520	x	618	x	7/10
500	25	520	x	625	x	7/10
500	40	520	x	628	x	7/10
600	6	620	x	680	x	7/10
600	10	620	x	695	x	7/10
600	16	620	x	735	x	7/10
600	25	620	x	730	x	7/10
600	40	620	x	745	x	7/10
700	6	720	x	785	x	8/11
700	10	720	x	810	x	8/11
700	16	720	x	805	x	8/11
700	25	720	x	830	x	8/11
700	40	720	x	850	x	8/11
800	6	820	x	890	x	8/11
800	10	820	x	915	x	8/11
800	16	820	x	910	X	8/11
800	25	820	x	940	x	8/11
800	40	820	x	970	x	8/11
900	6	920	x	990	x	8/11
900	10	920	x	1015	x	8/11
900	16	920	x	1010	x	8/11
900	25	920	x	1040	x	8/11
900	40	920	x	1080	X	8/11
1000	6	1020	x	1090	X	8/11
1000	10	1020	x	1120	X	8/11
1000	16	1020	x	1125	X	8/11
• 1000	40	1020	x	1190	X	8/11
1100	10	1120	x	1215	X	8/11
• 1200	2,5	1220	x	1290	X	8/11
1200	10	1220	x	1341	X	8/11
1200	16	1220	x	1342	X	8/11
• 1200	25	1220	x	1360	X	8/11
• 1200	40	1220	x	1395	X	8/11
• 1400	16	1454	x	1540	x	8/11

• Available on request


G-ST-P/S

DIVERSE RANGE OF APPLICATIONS

G-ST-P/S (Special dimensions)

Diameter Nominal	Dimensions in mm				
DN	d ₁	x	d ₂	x	s ₁ /s ₂
40	38	x	92	x	3 / 4
50	50	x	107	x	4 / 5
65	66	x	127	x	4 / 5
80	76	x	142	x	4 / 5
• 80	84	x	133	x	4 / 5
100	100	x	162	x	4 / 5
125	125	x	192	x	5 / 6
150	150	x	218	x	5 / 6
150	144	x	218	x	6 / 8
175	175	x	235	x	6 / 8
200	182	x	275	x	6 / 8
200	200	x	273	x	6 / 8
250	228	x	328	x	6 / 8
250	250	x	328	x	6 / 8
300	275	x	378	x	6 / 8
300	300	x	378	x	6 / 8
350	285	x	438	x	7 / 10
350	330	x	438	x	7 / 10
350	340	x	490	x	7 / 10
350	340	x	617	x	7 / 10
350	396	x	444	x	6 / 8
400	372	x	490	x	7 / 10
400	324	x	490	x	7 / 10
400	400	x	490	x	7 / 10
500	465	x	595	x	7 / 10
600	586	x	695	x	7 / 10
• 600	630	x	680	x	7 / 10
700	661	x	810	x	8 / 11
700	690	x	755	x	8 / 11
800	749	x	915	x	8 / 11

• Available on request



G-ST-P/S (Special dimensions)

Dimensions for flanges of VCI-tanks


In accordance with construction guideline C2.1.1

Diameter Nominal	Dimensions in mm				
DN	d ₁	x	d ₂	x	s ₁ /s ₂
500	510	x	577	x	7/10
600	610	x	677	x	7/10
600	610	x	717	x	7/10
700	710	x	782	x	8/11
800	810	x	887	x	8/11



G-ST-P/S

DIVERSE RANGE OF APPLICATIONS



G-ST-P/S

Für ASME B 16.5 Flanges

Diameter Nominal	Dimensions in mm/ Nominal pressure up to 150 lbs					Dimensions in mm / Nominal pressure up to 300 lbs				
	NPS	d ₁	x	d ₂	x	s ₁ /s ₂	d ₁	x	d ₂	x
1/2"	21	x	45	x	3 / 4	20	x	51	x	3 / 4
3/4"	27	x	54	x	3 / 4	27	x	64	x	3 / 4
1"	33	x	64	x	3 / 4	33	x	70	x	3 / 4
1 1/4"	42	x	73	x	3 / 4	42	x	80	x	3 / 4
1 1/2"	48	x	83	x	3 / 4	48	x	92	x	3 / 4
2"	60	x	102	x	4 / 5	60	x	108	x	4 / 5
2 1/2"	73	x	121	x	4 / 5	73	x	127	x	4 / 5
3"	89	x	133	x	4 / 5	89	x	146	x	4 / 5
3 1/2"	102	x	159	x	4 / 5	102	x	162	x	4 / 5
4"	115	x	171	x	5 / 6	115	x	178	x	5 / 6
5"	140	x	193	x	5 / 6	140	x	213	x	5 / 6
6"	168	x	219	x	6 / 8	168	x	247	x	6 / 8
8"	219	x	276	x	6 / 8	219	x	305	x	6 / 8
10"	273	x	337	x	6 / 8	273	x	359	x	6 / 8
12"	325	x	406	x	6 / 8	325	x	419	x	6 / 8
14"	356	x	448	x	7 / 10	356	x	482	x	7 / 10
16"	406	x	512	x	7 / 10	406	x	537	x	7 / 10
18"	457	x	547	x	7 / 10	457	x	594	x	7 / 10
20"	508	x	604	x	7 / 10	508	x	651	x	7 / 10
24"	610	x	715	x	5.5 / 8	610	x	772	x	7 / 10

G-ST-P/S

For ASME B 16.47 Series A Flanges

Diameter Nominal	Dimensions in mm / Nominal pressure up to 150 lbs					Dimensions in mm / Nominal pressure up to 300 lbs					
	NPS	d ₁	x	d ₂	x	s ₁ /s ₂	d ₁	x	d ₂	x	s ₁ /s ₂
26"	665	x	771	x	7 / 10		665	x	832	x	7 / 10
28"	720	x	829	x	8 / 11		720	x	895	x	8 / 11
30"	770	x	880	x	8 / 11		770	x	949	x	8 / 11
32"	820	x	937	x	8 / 11		820	x	1003	x	8 / 11
34"	865	x	987	x	8 / 11		856	x	1054	x	8 / 11
36"	920	x	1045	x	8 / 11		920	x	1114	x	8 / 11
•38"	965	x	1108	x	8 / 11		965	x	1051	x	8 / 11
40"	1020	x	1159	x	8 / 11		•1020	x	1111	x	8 / 11
42"	1070	x	1216	x	8 / 11		•1070	x	1162	x	8 / 11
44"	1120	x	1273	x	8 / 11		•1120	x	1216	x	8 / 11
•46"	1170	x	1324	x	8 / 11		•1170	x	1270		8 / 11
48"	1220	x	1381	x	8 / 11		•1220	x	1321	x	8 / 11
50"	1270	x	1432	x	8 / 11		•1270	x	1375	x	8 / 11
52"	1320	x	1489	x	8 / 11		•1320	x	1425	x	8 / 11
54"	1370	x	1546	x	8 / 11		•1370	x	1489	x	8 / 11
56"	1430	x	1603	x	8 / 11		•1430	x	1540	x	8 / 11
•58"	1475	x	1660	x	8 / 11		•1475	x	1590	x	8 / 11
60"	1530	x	1711	x	8 / 11		1530	x	1641	x	8 / 11


• Available on request

G-ST-P/S

For ASME B 16.47 Flansche Series B Flanges

Diameter Nominal	Dimensions in mm / Nominal pressure up to 150 lbs				
NPS	d ₁	x	d ₂	x	s ₁ /s ₂
28"	720	x	773	x	8 / 11
30"	770	x	824	x	8 / 11
32"	820	x	878	x	8 / 11
36"	920	x	984	x	8 / 11

G-ST-P/K PLASTIC FLANGES



G-ST-P/K

For thermoplastic flange connections
(PVC, PP, PE, PVDF)

Flange		Pipe outside Ø		Dimensions in mm			
DN	mm	d ₁	x	d ₂	x	s ₁ /s ₂	
10	16	16	x	46	x	3 / 4	
15	20	20	x	51	x	3 / 4	
20	25	25	x	61	x	3 / 4	
25	32	32	x	71	x	3 / 4	
32	40	40	x	82	x	3 / 4	
40	50	50	x	92	x	3 / 4	
50	63	63	x	107	x	4 / 5	
65	75	75	x	127	x	4 / 5	
80	90	90	x	142	x	4 / 5	
100	110	110	x	162	x	5 / 6	
125	125	125	x	192	x	5 / 6	
125	140	140	x	192	x	5 / 6	
150	160	160	x	218	x	6 / 8	
200	200	200	x	273	x	6 / 8	
200	225	225	x	273	x	6 / 8	
250	250	250	x	303	x	6 / 8	
250	250	250	x	328	x	6 / 8	
250	280	280	x	328	x	6 / 8	
300	315	315	x	378	x	6 / 8	
350	355	355	x	438	x	7 / 10	
400	400	400	x	489	x	7 / 10	

G-ST-P/K


For plastic pressure pipelines made of PVDF with
plastic stub and loose flanges

Flange		Pipe outside Ø		Dimensions in mm				
DN	PN	mm	SDR	d ₁	x	d ₂	x	s ₁ /s ₂
20	16	25	21	24	x	61	x	3 / 4
25	16	32	21	30	x	71	x	3 / 4
32	16	40	21	37	x	82	x	3 / 4
40	16	50	21	46	x	92	x	3 / 4
50	16	63	21	61	x	107	x	4 / 5
65	16	75	21	73	x	127	x	4 / 5
65	10	75	33	69	x	127	x	4 / 5
80	10-16	90	33	84	x	142	x	4 / 5
100	16	110	21	104	x	162	x	5 / 6
100	10	125	33	123	x	162	x	5 / 6
125	10	140	33	137	x	192	x	5 / 6
125	16	140	21	127	x	192	x	5 / 6
150	10	160	33	156	x	218	x	6 / 8
150	16	160	21	146	x	218	x	6 / 8
150	10	180	33	177	x	218	x	6 / 8
200	10	200	33	196	x	273	x	6 / 8
200	16	200	21	181	x	273	x	6 / 8
200	10	225	33	220	x	273	x	6 / 8
200	16	225	21	203	x	273	x	6 / 8
250	10	280	33	274	x	328	x	6 / 8

G-ST-P/K
PLASTIC FLANGES

G-ST-P/K

For plastic pressure pipelines made of PE and PP with plastic stub and loose flange
Flange dimension similar to DIN 2501 PN10



Flange	Pipe outside Ø		Dimensions in mm				
DN	mm	SDR	d ₁	x	d ₂	x	s ₁ /s ₂
20	25	11	22	x	61	x	3 / 4
20	25	7,4	24	x	61	x	3 / 4
25	32	11	28	x	71	x	3 / 4
25	32	7,4	23	x	71	x	3 / 4
32	40	11	34	x	82	x	3 / 4
32	40	7,4	29	x	82	x	3 / 4
40	50	17	46	x	92	x	3 / 4
40	50	11	42	x	92	x	3 / 4
40	50	7,4	36	x	92	x	3 / 4
50	63	17	58	x	107	x	4 / 5
50	63	11	53	x	107	x	4 / 5
50	63	7,4	45	x	107	x	4 / 5
65	75	17	69	x	127	x	4 / 5
65	75	11	63	x	127	x	4 / 5
65	75	7,4	54	x	127	x	4 / 5
80	90	17	84	x	142	x	4 / 5
80	90	11	76	x	142	x	4 / 5
80	90	7,4	65	x	142	x	4 / 5
100	110	33	104	x	162	x	5 / 6
100	110	17	100	x	162	x	5 / 6
100	110	11	93	x	162	x	5 / 6
100	110	7,4	80	x	162	x	5 / 6
100	125	33	123	x	162	x	5 / 6
100	125	17	114	x	162	x	5 / 6
100	125	11	105	x	162	x	5 / 6
100	125	7,4	90	x	162	x	5 / 6
125	140	33	137	x	192	x	5 / 6
125	140	17	127	x	192	x	5 / 6
125	140	11	117	x	192	x	5 / 6
125	140	7,4	101	x	192	x	5 / 6

- 1) The nominal width of the flange does not have to correspond to the nominal width of the pipeline.
- 2) SDR = Standard Dimension Ratio
(Ratio pipe-outside Ø / wall thickness)

Flange	Pipe outside Ø		Dimensions in mm				
DN	mm	SDR	d ₁	x	d ₂	x	s ₁ /s ₂
125	140	7,4	101	x	192	x	5 / 6
150	160	33	156	x	218	x	6 / 8
150	160	17	146	x	218	x	6 / 8
150	160	11	135	x	218	x	6 / 8
150	160	7,4	116	x	218	x	6 / 8
150	180	33	177	x	218	x	6 / 8
150	180	17	164	x	218	x	6 / 8
150	180	11	151	x	218	x	6 / 8
150	180	7,4	130	x	218	x	6 / 8
200	200	33	196	x	273	x	6 / 8
200	200	17	181	x	273	x	6 / 8
200	200	11	168	x	273	x	6 / 8
200	200	7,4	145	x	273	x	6 / 8
200	225	33	220	x	273	x	6 / 8
200	225	17	203	x	273	x	6 / 8
200	225	11	188	x	273	x	6 / 8
250	250	33	243	x	328	x	6 / 8
250	250	17	226	x	328	x	6 / 8
250	250	11	208	x	328	x	6 / 8
250	280	33	274	x	328	x	6 / 8
250	280	17	252	x	328	x	6 / 8
250	280	11	233	x	328	x	6 / 8
300	315	33	306	x	378	x	6 / 8
300	315	17	283	x	378	x	6 / 8
300	315	11	262	x	378	x	6 / 8
350	355	17	319	x	438	x	6 / 8
350	355	11	294	x	438	x	6 / 8
400	400	17	359	x	489	x	6 / 8
400	400	11	331	x	489	x	6 / 8
500	450	17	403	x	594	x	7/10
500	450	11	372	x	594	x	7/10
500	500	17	447	x	594	x	7/10
500	500	11	413	x	594	x	7/10
600	560	17	494	x	695	x	7/10
600	560	11	462	x	695	x	7/10
600	560	11	451	x	695	x	7/10
600	630	17	555	x	695	x	7/10
600	630	11	519	x	695	x	7/10



RUBBER-STEEL-PROFILE-GASKETS

FOR STEEL FLANGE CONNECTIONS IN THE FORCE SHUNT CONNECTION

The successful fusion of two opposing philosophies of poetry

The **G-ST-Profile-Gasket-Program** consistently shows adequate deformation and adaptation at small surface pressures.


If extreme loads due to acting forces have to be compensated for in the installed condition, the type G-ST-P/KN offers the optimum solution.

The external steel ring chambers the O-ring/flat seal lip and protects it completely.

High surface pressures on the rubber lip, other mechanical interference or blow-out under high operating pressures and pressure surges are impossible.


In the case of partially coated flanges, the sensitive surfaces are protected.

G-ST-P/KN profile gaskets are approved in accordance with DIN 30690 for GAS applications at pressures up to 100 bar.



Typical applications


- + Rubberized assemblies in chemical and power plants or Systems with high operating pressures
- + Up to 100 bar
- + Materials: EPDM/NBR/FKM Back-up ring: S235JR galvanized/ 1.4301/1.4571 (others on request)



G-ST-P/KN FORCE SHUNT

G-ST-P / KN based on DIN 2690

For steel flange connections in force shunt and gas applications according to DIN 30690



PN	6	10	16	25	40	63	100	
DN	d ₁	d ₄	d ₄	d ₄	d ₄	d ₄	d ₄	s ₁ /s ₂
10	18		45	45	45	45	56	5 / 3
15	22		50	50	50	50	61	5 / 3
20	28		60	60	60	60		5 / 3
25	35		70	70	70	70	82	5,5 / 3,5
32	43		82	82	82	82		5,5 / 3,5
40	49		92	92	92	92	103	5,5 / 3,5
50	61		107	107	107	107	113	5,5 / 3,5
65	77		127	127	127	127	137	5,5 / 3,5
80	90		142	142	142	142	148	5,5 / 3,5
100	115		162	162	168	168	174	8 / 5
125	141		192	192	195	195	210	8 / 5
150	169		218	218	225	225	247	8 / 5
175	195		248	248	255	267	277	8 / 5
200	220		273	273	285	292	309	8 / 5
250	274		328	330	342	353	364	8 / 5
300	325		378	385	402	418	424	8 / 5
350	368		438	445	458	475	486	8 / 5
400	420	473	490	497	515	547	543	8 / 5
450	470		540	557	565	572		10 / 6
500	520	578	595	618	625	628	657	10 / 6
600	620	680	695	735	730	745	764	10 / 6
700	720	784	810	805	830	850	879	10 / 6
800	820	890	915	910	940	970	988	10 / 6
900	920	990	1015	1010	1040	1080	1108	10 / 6
1000	1020		1120	1125	1150	1190	1220	10 / 6
1200	1220	1307	1340	1340	1360	1395	1452	10 / 6
1400	1420		1545	1540	1575	1615		12 / 8
1600	1620	1724	1770	1760	1795	1830		12 / 8
1800	1820		1970	1960	2000			12 / 8
2000	2020		2180	2165	2230			12 / 8
2200	2220	2348	2380		2375			12 / 8
2400	2420	2558	2590	2585				12 / 8
2600	2620		2790	2785				12 / 8
2800	2820		3010					12 / 8
3000	3020		3225					12 / 8


G-ST-P/KN

FORCE SHUNT

G-ST-P / KN based on ASME B16.21

For steel flange connections in force shunt and gas applications according to DIN 30690

Similar to ASME B16.21 for ASME B16.5 flanges



Class		150	300	400	600	900	
NPS	d ₁	d ₄	d ₄	d ₄	d ₄	d ₄	s ₁ /s ₂
1/2"	16	45	51	51	51	61	5 / 3
3/4"	22	54	64	64	64	67	5 / 3
1"	28	64	70	70	70	76	5 / 3
1 1/4"	35	73	80	80	80	86	5,5 / 3,5
1 1/2"	43	83	93	93	93	95	5,5 / 3,5
2"	61	102	108	108	108	140	5,5 / 3,5
2 1/2"	77	121	127	127	127	162	5,5 / 3,5
3"	90	134	146	146	146	165	5,5 / 3,5
3 1/2"	102	159	162	159	159		8 / 5
4"	115	172	178	175	191	203	8 / 5
5"	141	194	213	210	238	245	8 / 5
6"	169	220	248	245	264	286	8 / 5
8"	220	277	305	302	318	356	8 / 5
10"	274	337	359	356	397	432	8 / 5
12"	325	407	419	416	454	496	8 / 5
14"	368	448	483	480	489	518	8 / 5
16"	420	512	537	534	562	572	8 / 5
18"	470	547	594	591	610	635	10/6
20"	520	604	651	645	680	696	10/6
24"	620	715	772	766	788	835	10/6


Materials

EPDM, NBR, FKM, more gaskets on request

Support ring

S235JR galvanisiert / 1.4301 / 1.4571

Further support rings on request




G-ST-P/KN FORCE SHUNT

G-ST-P / KN based on ASME B 16.21

For steel flange connections in force shunt and gas applications according to DIN 30690

Similar to ASME B 16.21 for ASME B 16.47 Series A Flanges



Class	150	300	400	600
-------	-----	-----	-----	-----

NPS	d ₁	d ₄	d ₄	d ₄	d ₄	s ₁ /s ₂
26"	665	771	832	829	864	10/6
28"	720	829	895	889	911	10/6
30"	770	880	949	943	968	10/6
32"	820	937	1003	1000	1019	10/6
34"	865	987	1054	1051	1070	10/6
36"	920	1045	1114	1114	1127	10/6
38"	965	1108	1051	1070	1102	10/6
40"	1020	1159	1111	1124	1152	10/6
42"	1070	1216	1162	1175	1216	10/6
44"	1120	1273	1216	1229	1267	10/6
46"	1170	1324	1270	1286	1324	10/6
48"	1220	1381	1321	1343	1387	10/6
50"	1270	1432	1375	1400	1445	12/8
52"	1320	1489	1425	1451	1495	12/8
54"	1370	1546	1489	1515	1552	12/8
56"	1430	1603	1540	1565	1610	12/8
58"	1475	1660	1590	1616	1660	12/8
60"	1530	1711	1641	1680	1730	12/8

G-ST-P / KN

For steel flange connections in force shunt and gas applications according to DIN 30690

Similar to ASME B 16.21 for ASME B 16.47 Series B flanges

Class	150	300	400	600
-------	-----	-----	-----	-----

NPS	d ₁	d ₄	d ₄	d ₄	d ₄	s ₁ /s ₂
26"	665	725	771	746	765	10/6
28"	720	776	825	800	819	10/6
30"	770	827	886	857	879	10/6
32"	820	881	939	911	933	10/6
34"	865	935	993	962	997	10/6
36"	920	987	1047	1022	1047	10/6
38"	965	1044	1098			10/6
40"	1020	1095	1149			10/6
42"	1070	1146	1200			10/6
44"	1120	1196	1251			10/6
46"	1170	1255	1317			10/6
48"	1220	1306	1368			10/6
50"	1270	1357	1419			12/8
52"	1320	1408	1470			12/8
54"	1370	1463	1530			12/8
56"	1430	1514	1593			12/8
58"	1475	1579	1655			12/8
60"	1530	1630	1704			12/8

G-ST-P/HTB


HIGHER THERMAL LOAD CAPACITY

G-ST-P / HTB based on DIN 1514-1 and DIN 2690

For steel flange connections in HTB (higher thermal load capacity) and piping systems, if necessary with connected fire extinguishing systems.

DVGW approved up to 5 bar according to DIN 30653 (formerly VP401)

Elastomer sealing lip made of NBR material, approved to DIN EN 682
Support ring comb-profiled, stainless steel 1.4571, with 0.5 mm graphite coating on both sides.



Diameter Nominal	Nominal pressure	Dimensions in mm				
DN	PN	d ₁	x	d ₄	x	s ₁ /s ₂
15	10-40	22	x	50	x	5 / 4
20	10-40	28	x	60	x	5 / 4
25	10-40	35	x	71	x	5,5/4,5
32	10-40	43	x	82	x	5,5/4,5
40	10-40	49	x	92	x	5,5/4,5
50	10-40	61	x	107	x	5,5/4,5
65	10-40	77	x	127	x	5,5/4,5
80	10-40	90	x	142	x	5,5/4,5
100	10-16	115	x	162	x	8/6
125	10-16	141	x	192	x	8/6
150	10-16	169	x	218	x	8/6
200	10-16	220	x	273	x	8/6
200	25	220	x	284	x	8/6
250	16	274	x	329	x	8/6
300	10	324	x	378	x	8/6



G-ST-P/OE CUSTOM GASKETS









G-ST-P / OE

Freely dimensionable gaskets with open steel insert

Thanks to their innovative design principle, profile gaskets are suitable for making flanged joints that have a weak static design operationally safe without additional effort.

In apparatus and tank construction, for example, there are often narrow sealing strips combined with a coarse bolt hole pattern. For these special cases, but also for any similarly designed construction, type **G-ST-P/OE** offers an excellent solution.

According to your specifications, we manufacture the appropriate profile gasket from elastomer and stainless steel profiles.



Elastomer lip

Others on request


Available materials

EPDM NBR FKM Silikon

Flat steel insert made of 1.4301

Others on request

Minimum inner diameter = 160 mm



G-ST/WEDGE RING INFINITELY ADJUSTABLE

G-ST-P / Wedge ring

The quick help for adjustment problems

The KROLL & ZILLER G-ST wedge ring is ideal for making adjustments during assembly in the event of misalignment or excessive installation play. The shell design with integrated elastomer gasket offers the possibility of continuously variable angles between 0° and 8°.

The ideal combination with G-ST gaskets is a must for the installer, as this makes time savings during assembly and operationally reliable flange sealing a real advantage.



The advantages at a glance

- + Bridging of gaps between flanges
- + Stepless compensation of flange misalignments and mounting errors from 0° to 8°
- + Certified for use in contact with drinking water


Diameter Nominal	Dimensions in mm				PN10		Weight
DN	d ₁	x	d ₂	x	s bei 0°	s bei 8°	kg
40	45	x	89	x	23	29	0,6
50	58	x	102	x	24	31	0,8
65	71	x	127	x	25	34	1,4
80	89	x	142	x	27	37	1,7
100	108	x	162	x	27	38	2,0
125	133	x	192	x	30	43	3,2
150	163	x	218	x	33	48	4,1
200	216	x	273	x	37	56	5,4
250	267	x	328	x	41	64	7,7
300	318	x	378	x	45	71	9,7
350	368	x	438	x	53	84	17,6
400	420	x	490	x	57	91	19,3
500	520	x	595	x	66	108	32,1
600	605	x	695	x	73	120	40,3
700	710	x	810	x	84	141	76,0
800	808	x	917	x	92	156	99,0
900	910	x	1015	x	100	171	121,0
• 1000	1011	x	1128	x	111	189	130,0
• 1200	1214	x	1341	x	127	221	216,4

- Available on request

Diameter Nominal	Dimensions in mm				PN10		Weight
NPS	d ₁	x	d ₂	x	s bei 0°	s bei 8°	kg
2"	55	x	102	x	24	31	0,92
2 1/2"	68	x	121	x	27	35	1,39
3"	84	x	133	x	28	37	1,54
4"	110	x	171	x	29	41	2,61
6"	163	x	219	x	35	50	3,89
8"	214	x	276	x	39	58	6,16
10"	268	x	337	x	43	67	9,5
12"	320	x	406	x	49	77	15,9



Materials: Elastomer gasket available in various materials.



GASKETS FOR PIPELINE CONSTRUCTION

THE MANUFACTURING PROCESS AT KROLL & ZILLER



Production of our own rubber compounds

Production of the specially developed KROLL & ZILLER rubber compound by mixing, rolling, calendering and granulating. The end result is a granulate that can be ideally processed by our process technology.



Production of inserts

Production of inserts from various materials using CNC laser cutting technology. Larger diameters are welded afterwards. In a next step, the inserts are prepared for the vulcanization process by priming and covering. This is necessary to create a good and inseparable bond between the elastomer (rubber) and the metal insert.



Extrusion

The granules produced are shaped by the extruder, and the insert is placed directly in the raw rubber mixture. The gasket blank is ready.


GASKETS FOR PIPELINE CONSTRUCTION

THE MANUFACTURING PROCESS AT KROLL & ZILLER



Vulcanization

KROLL & ZILLER has a huge stock of molds in which all possible standard dimensions of various standards are available. The blank, including the insert, is placed in such a mold and vulcanized by our vulcanizing presses at an adjusted temperature and pressure. This is how caoutchouc becomes rubber.



Large storage and optimal delivery capacity


A large and well-stocked storage is the guarantor of fast delivery. The logistics department with its own joinery packs and ships all over the world.




Technical support

Whether you have a technical question or would like more detailed information about our gaskets, our technical support team is here to help.

Our experienced team supports you in the design and calculation of flange connections with a holistic view of the area to be sealed.



NOTES





HIGH QUALITY
MADE IN GERMANY



KROLL & ZILLER GmbH & Co. KG

Reisholzstraße 15
40721 Hilden

Phone: +49 2103 951-0
Fax: +49 2103 951-509

info@kroll-ziller.de
www.kroll-ziller.com

The technical specifications correspond to the latest state of the art. We reserve the right to make changes in construction and design in the interest of progress. We ask for your understanding that no liability can be accepted for printing errors or mistakes. No part of this publication may be reproduced in any form or by any means without our express permission.

KZ-GK-03.23_EN

Hereby all previous catalogs become invalid.



Scan QR code and
download PDF catalog.

